

Borough of Mount Arlington  
**MUNICIPAL STORMWATER  
MANAGEMENT PLAN**

MORRIS COUNTY, NEW JERSEY  
FEBRUARY 2009

**BOROUGH OF MT. ARLINGTON, MORRIS COUNTY, NEW JERSEY**

Prepared for: The Borough of Mount Arlington  
419 Howard Boulevard  
Mt. Arlington, NJ 07856

Prepared By: Suburban Consulting Engineers, Inc.  
100 Valley Road, Suite 202  
Mount Arlington, New Jersey 07856

Our Project No. SCE-2485.1



DAREN J. PHIL, PE, PP, CME - LIC. # 36191  
BOROUGH ENGINEER

2-2-09

DATE

**Suburban Consulting Engineers, Inc.**

100 Valley Road, Suite 202  
Mount Arlington, New Jersey 07856  
Tel: (973) 398-1776  
Fax: (973) 398-2121

E-Mail: [info@suburbanconsulting.com](mailto:info@suburbanconsulting.com)

Website: <http://www.suburbanconsulting.com>

## INTRODUCTION

This Municipal Stormwater Management Plan (MSWMP) documents the strategy for Mount Arlington Borough ("the Borough") to address stormwater-related impacts. The creation of this plan is required by N.J.A.C. 7:14A-25 Municipal Stormwater Regulations. This plan contains all of the required elements described in N.J.A.C. 7:8 Stormwater Management Rules. The plan addresses groundwater recharge, stormwater quantity, and stormwater quality impacts by incorporating stormwater design and performance standards for new major development, defined as projects that disturb one or more acre of land. These standards are intended to minimize the adverse impact of stormwater runoff on water quality and water quantity and the loss of groundwater recharge that provides baseflow in receiving water bodies. The plan describes long-term operation and maintenance measures for existing and future stormwater facilities.

The plan also addresses the review and update of existing ordinances, the Borough Master Plan, and other planning documents to allow for project designs that include low impact development techniques. The final component of this plan is a mitigation strategy for when a variance or exemption of the design and performance standards is sought. As part of the mitigation section of the stormwater plan, specific stormwater management measures are identified to lessen the impact of existing development.

## **TABLE OF CONTENTS**

<b><u>SECTION</u></b>	<b><u>PAGE</u></b>
INTRODUCTION	
SECTION I Goals .....	I-1
SECTION II Stormwater Discussion .....	II-1
SECTION III Background .....	III-1
SECTION IV Design and Performance Standards .....	IV-1
SECTION V Plan Consistency .....	V-1
SECTION VI Nonstructural Stormwater Management Strategies .....	VI-1
SECTION VII Land Use/Build-Out Analysis .....	VII-1
SECTION VIII Mitigation Plans .....	VIII-1

### **FIGURES**

FIGURE 1	Groundwater Recharge in the Hydrologic Cycle
FIGURE 2	Borough and Its Waterways
FIGURE 2A	Borough Waterways by Surface Classification
FIGURE 3	Borough Boundaries on USGS Quadrangles
FIGURE 4	Groundwater Recharge Areas in the Borough
FIGURE 5	Wellhead Protection Areas in the Borough
FIGURE 6	Existing Land Use/Land Cover within the Borough
FIGURE 7	Hydrologic Units (HUC14s) within the Borough
FIGURE 8	Zoning Districts within the Borough
FIGURE 9	Constrained Land (Wetlands and Water Land Uses) within the Borough

### **APPENDICES**

APPENDIX 1	Proposed Stormwater Control Ordinance
------------	---------------------------------------

## **I. GOALS**

The goals of this MSWMP are to:

1. Reduce flood damage, including damage to life and property;
2. Minimize, to the extent practical, any increase in stormwater runoff from any new development;
3. Reduce soil erosion from any development or construction project;
4. Assure the adequacy of existing and proposed culverts and bridges, and other in-stream structures;
5. Maintain groundwater recharge;
6. Prevent, to the greatest extent feasible, an increase in nonpoint pollution;
7. Maintain the integrity of stream channels for their biological functions, as well as for drainage;
8. Minimize pollutants in stormwater runoff from new and existing development to restore, enhance, and maintain the chemical, physical, and biological integrity of the waters of the state, to protect public health, to safeguard fish and aquatic life and scenic and ecological values, and to enhance the domestic, municipal, recreational, industrial, and other uses of water; and
9. Protect public safety through the proper design and operation of stormwater basins.

To achieve these goals, this plan outlines specific stormwater design and performance standards for new development. Additionally, the plan proposes stormwater management controls to address impacts from existing development. Preventative and corrective maintenance strategies are included in the plan to ensure long-term effectiveness of stormwater management facilities. The plan also outlines safety standards for stormwater infrastructure to be implemented to protect public safety.




## II. STORMWATER DISCUSSION

Land development can dramatically alter the hydrologic cycle (See Figure 1) of a site and, ultimately, an entire watershed. Prior to development, native vegetation can either directly intercept precipitation or draw that portion that has infiltrated into the ground and return it to the atmosphere through evapotranspiration. Development can remove this beneficial vegetation and replace it with lawn or impervious cover, reducing the site's evapotranspiration and infiltration rates. Clearing and grading a site can remove depressions that store rainfall. Construction activities may also compact the soil and diminish its infiltration ability, resulting in increased volumes and rates of stormwater runoff from the site. Impervious areas that are connected to each other through gutters, channels, and storm sewers can transport runoff more quickly than natural areas.

This shortening of the transport or travel time quickens the rainfall-runoff response of the drainage area, causing flow in downstream waterways to peak faster and higher than natural conditions. These increases can create new and aggravate existing downstream flooding and erosion problems and increase the quantity of sediment in the channel. Filtration of runoff and removal of pollutants by surface and channel vegetation is eliminated by storm sewers that discharge runoff directly into a stream. Increases in impervious area can also decrease opportunities for infiltration which, in turn, reduces stream base flow and groundwater recharge. Reduced base flows and increased peak flows produce greater fluctuations between normal and storm flow rates, which can increase channel erosion. Reduced base flows can also negatively impact the hydrology of adjacent wetlands and the health of biological communities that depend on base flows. Finally, erosion and sedimentation can destroy habitat from which some species cannot adapt.

**Figure 1: Groundwater Recharge in the Hydrologic Cycle**



Source: New Jersey Geological Survey Report GSR-32.

In addition to increases in runoff peaks, volumes, and loss of groundwater recharge, land development often results in the accumulation of pollutants on the land surface that runoff can mobilize and transport to streams. New impervious surfaces and cleared areas created by development can accumulate a variety of pollutants from the atmosphere, fertilizers, animal wastes, and leakage and wear from vehicles. Pollutants can include metals, suspended solids, hydrocarbons, pathogens, and nutrients.

In addition to increased pollutant loading, land development can adversely affect water quality and stream biota in more subtle ways. For example, stormwater falling on impervious surfaces or stored in detention or retention basins can become heated and raise the temperature of the downstream waterway, adversely affecting cold water fish species such as trout. Development can remove trees along stream banks that normally provide shading, stabilization, and leaf litter that falls into streams and becomes food for the aquatic community.



### III. BACKGROUND

The Borough of Mount Arlington is 2.9 miles in size and is located in the northern part of Morris County. Its neighboring municipalities in Morris County are Jefferson Township and Roxbury Township and its neighboring municipality in Sussex County is the Borough Hopatcong. The main highways servicing the Borough are County Route 615, otherwise known as Howard Boulevard and County Route 616, otherwise known as Mt. Arlington Boulevard.

The Borough is a primarily suburban community with residential land and commercial uses being most prominent. The Borough population has been increasing over several decades, most likely as a result of Mt. Arlington's proximity to Interstate 80 and easy access to employment centers to the east. The U.S. Census population for the Borough was recorded at 3,630 persons in 1990. The population of Mount Arlington had risen to 4,663 as of the 2000 Census, resulting in a population increase of 28.65%. This and future population increases could result in a considerable demand on the existing infrastructures of the Borough as a result of new development and redevelopment. New development would cause changes to occur to the landscape that will increase stormwater runoff volumes and pollutant loads to the waterways of the municipality.

The Borough is on the southerly shore of Lake Hopatcong which drains most of the Borough to the Musconetcong. The southwesterly portion of the Borough drains towards the Lamington River, which drains to the North and South branches of the Raritan River. Figure 2 illustrates the waterways in the Borough and Figure 2A specifies the current surface water classifications for the Borough. There are no Category One (C1) designation for waterbodies within the Borough as of this report.

A ridge forming the southeastern border of the Borough has required the town to be built on the northward facing steep slopes and shoreline overlooking Lake Hopatcong. Very little of the Borough is flat and as such does not lend itself to ease of development. For reference, Figure 3 depicts the Township boundary and topography on the USGS quadrangle maps.

#### Water Quality

The NJDEP and other regulatory agencies collect water quality chemical data on the streams in the state. The New Jersey Integrated Water Quality Monitoring and Assessment Report (305(b) and 303(d)) (Integrated List) is required by the federal Clean Water Act to be prepared biennially and is a valuable source of water quality information. This combined report presents the extent to which New Jersey waters are attaining water quality standards, and identifies waters that are impaired. The additional waterways listed on the Integrated List with the NJDEP and other regulatory agency data are the following:

- Lake Hopatcong

Private and Public beaches along Lake Hopatcong were tested for fecal coliform by the Mount Arlington Board of Health. Lake Hopatcong was found to be attaining the water quality standard and no use is threatened. Lake Hopatcong has a TMDL (total maximum daily load) assigned to address eutrophic conditions on the lake. The lake appears on Sublist 4 of the Integrated List.

Eutrophication is a process that can be accelerated by excessive inputs of nutrients and suspended sediments from the surrounding watersheds. Eutrophic conditions include the increase of algal bloom due to the excess nutrients. As a result, fish species may not be able to survive in the oxygen starved environment and odor and taste problems may occur. There are many potential sources of nutrients to lakes, including fertilizers in runoff from lawns, golf courses and agricultural areas, pet and wildlife wastes and malfunctioning septic systems. It should be noted that the portion of the Borough located in the Lake Hopatcong lakeshed is primarily suburban and is seen as a major contributor of nutrients or sediment to the lake. Phosphorus studies have been instituted at the lake to reduce and limit the amount of phosphorus entering the lake from runoff and failing septic systems.

### Water Quantity

As the imperviousness increases in the Borough, the peak and volumes of stream flows are also increased. The increased amount of water results in stream bank erosion, which results in unstable areas along stream banks, and degraded stream habitats. By increasing the imperviousness of the Borough, groundwater recharge areas decrease, thereby decreasing base flows in streams during dry weather periods. Lower base flows can have a negative impact on instream habitats during the summer months. A map of the groundwater recharge areas is shown for reference in Figure 4. Wellhead protection areas, also areas to be considered for additional protection, are shown in Figure 5. Land Use Mapping for the Borough can be found in Figure 6

### Watershed Management Areas (WMAs)

The Borough of Mount Arlington is located within Watershed Management Area (WMA) 1- the Upper Delaware River Watershed (Figure 7). Within the Upper Delaware River Watershed, there are further drainage area designations delineated by hydraulic unit code (HUC) designations. The system starts with the largest possible drainage areas and progressively smaller subdivisions of the drainage area are delineated and numbered in a nested fashion. A drainage area with a hydrologic unit code (HUC) designation with 14 numbers, or HUC-14, is one of several sub watersheds of a larger watershed with 11 numbers, or a HUC-11.

Four HUC-11 divisions exist in Mount Arlington, the Musconetcong River (above Trout Brook), the Lamington River (above Rt. 10), the Raritan River (SB) above Spruce Run and the Rockaway River (Stephans Brook to Longwood Lake. Within Mount Arlington, three HUC-14s exists within the Musconetcong River HUC-11, Lake Hopatcong, Lamington River and Drakes Brook (above Eyland Ave) which is part of the Raritan River watershed.



#### **IV. DESIGN AND PERFORMANCE STANDARDS**

The Borough will adopt the design and performance standards for stormwater management measures as presented in N.J.A.C. 7:8-5 to minimize the adverse impact of stormwater runoff on water quality and water quantity and loss of groundwater recharge in receiving water bodies. The design and performance standards include the language for maintenance of stormwater management measures consistent with the stormwater management rules at N.J.A.C. 7:8-5.8 Maintenance Requirements, and language for safety standards consistent with N.J.A.C. 7:8-6 Safety Standards for Stormwater Management Basins. The ordinances will be submitted to the county for review and approval by April 1, 2006. A proposed draft of the Ordinance is included as Appendix A of this plan.

The Stormwater Management Rules stress performance standards for ground water recharge to increase the integrity of the state's aquifers. They establish a goal of maintaining 100 percent of the average annual groundwater recharge for new development projects.

In addition to recharge standards, the regulations also stress water quality controls, such as best management practices to reduce runoff of total suspended solids (TSS) by 80 percent and other pollutants up to the maximum extent feasible. The rules promote smart growth techniques, stressing low impact site designs for stormwater management systems that maintain natural vegetation and drainage and reduce clear-cutting and the unnecessary loss of trees.

## **V. PLAN CONSISTANCY**

The Borough is not within a Regional Stormwater Management Planning Area and no TMDLs have been developed for waters within the Borough at this time; therefore this plan does not need to be consistent with any regional stormwater management plans (RSWMPs) nor any TMDLs. If any RSWMPs or TMDLs are developed in the future, this Municipal Stormwater Management Plan will be updated to be consistent.

The Municipal Stormwater Management Plan is consistent with the Residential Site Improvement Standards (RSIS) at N.J.A.C. 5:21. The municipality will utilize the most current update of the RSIS in the stormwater management review of residential areas. This Municipal Stormwater Management Plan will be updated to be consistent with any future updates to the RSIS.

The Borough's Stormwater Management Ordinance requires all new development and redevelopment plans to comply with New Jersey's Soil Erosion and Sediment Control Standards. During construction, Borough inspectors will observe on-site soil erosion and sediment control measures and report any inconsistencies to the local Soil Conservation District.

## **VI. NONSTRUCTURAL STORMWATER MANAGEMENT STRATEGIES**

The master plan and ordinances of Mount Arlington Borough have been reviewed with regard to incorporating nonstructural stormwater management strategies. The review is detailed below and a list of relevant sections in the Borough land use regulations that are to be modified to incorporate nonstructural stormwater management strategies are provided. Once the ordinance texts are completed, they will be submitted to the county review agency for review and approval by April 1, 2006. A copy will be sent to the Department of Environmental Protection at the time of submission.

Article VI- Development Standards  
Chapter 17-22 Specific Improvements  
Subsection 17-22.1 Stormwater

This section of the ordinance discusses the requirements of the stormwater system. The type of piping, spacing of inlets and construction of manholes, inlets, headwalls, underdrains, and subbase outlet drains.

This section of the ordinance is not in contradiction of the new SWMP requirements and can be left in its' entirety for guidance in delegating the types of materials required for the installation of various storm drainage designs

Article IX Stormwater and Floodplain Regulations  
Chapter 17-38 and 17-39  
All subsections- In its' Entirety

This section of the ordinance discusses the requirements of the operation and control of stormwater facilities. It further directs the requirements of design and maintenance of these types of facilities. This entire section can be deleted from the ordinances and replaced with a new NJDEP formatted stormwater control ordinance that is attached to this Plan for review and will be adopted by the Borough Council to replace and be in conformance with the new stormwater regulations and Municipal Stormwater Management Plan requirements of the NJDEP.

## **VII. LAND USE/BUILD-OUT ANALYSIS**

No Build-Out Analysis for the Borough is necessary because the remaining developable land is in the Highlands Preservation Zone. Isolated lots (infill) throughout the Borough may be the only remaining developable lands left and with the recent installation of “city” sanitary sewers, these lots do not represent enough cumulative area to meet the build out analysis requirements.



## VIII. MITIGATION PLANS

Applicants seeking a variance or exemption from the stormwater management design and performance standards can identify, design and implement a compensating measure to mitigate impacts; complete a project identified by the municipality as equivalent to the environmental impact created by the exemption or variance; or provide funding for municipal projects that would address existing stormwater impacts. Presented below is a hierarchy of options.

Option 1: The preferred option is to identify a mitigation project within the same drainage area as the proposed development that directly compensates for the projected impact (recharge, quantity or quality) of the variance or exception. The project must provide additional groundwater recharge benefits, or protection from stormwater runoff quality or quantity from previously developed property that does not currently meet the design and performance standards outlined in the Municipal Stormwater Management Plan. The developer must ensure the long-term maintenance of the project, including the maintenance requirements under Chapters 8 and 9 of the NJDEP Stormwater BMP Manual and also listed in Section 8 of the Stormwater Control Ordinance.

The applicant must gain approval of the Borough Land Use Board and Engineer for the proposed project. More detailed information on potential projects can be obtained from the Borough Engineer. Additionally, the applicant must gain all necessary agreements and permits necessary to complete the mitigation project.

Option 2: If a suitable site cannot be located in the same drainage area as the proposed development, as discussed in Option 1, the mitigation project may provide mitigation that is not equivalent to the impacts for which the variance or exemption is sought, but that addresses the same issue. For example, if a variance is given because the 80 percent TSS requirement is not met, the selected project may address water quality impacts to prevent fecal impairment.

Option 3: The last option to an applicant is to provide funding for specific municipal projects within the municipality that would retrofit existing groundwater recharge, stormwater quality or stormwater quantity issues.

**APPENDIX 1 – PROPOSED STORMWATER CONTROL ORDINANCE**

**AN ORDINANCE OF THE MAYOR AND BOROUGH COUNCIL  
OF THE BOROUGH OF MOUNT ARLINGTON, IN THE COUNTY OF  
MORRIS, STATE OF NEW JERSEY, AMENDING CHAPTER 108, LAND  
DEVELOPMENT, TO REVISE ARTICLE IX, STORMWATER AND FLOOD  
PLAIN REGULATIONS, OF THE BOROUGH CODE TO ESTABLISH  
NEW MINIMUM STORMWATER MANAGEMENT REQUIREMENTS  
AND CONTROLS**

**BE IT ORDAINED**, by the Mayor and Borough Council of the Borough of Mount Arlington, County of Morris and State of New Jersey as follows:

**SECTION 1.** Section 39, Stormwater Control, of Article IX, Stormwater and Flood Plain Regulations, of Chapter 108, Land Development, of the Mount Arlington Code is hereby deleted in its entirety, and replaced by the following:

**§17-39 STORMWATER CONTROL**

**§17-39.1.** Policy statement, purpose and application of stormwater controls

**A. Policy Statement**

Flood control, groundwater recharge, and pollutant reduction through nonstructural or low impact techniques shall be explored before relying on structural BMPs. Structural BMPs should be integrated with nonstructural stormwater management measures and proper maintenance plans. Nonstructural measures include both environmentally sensitive site design and source controls that prevent pollutants from being placed on the site. Source control plans should be developed based upon physical site conditions and the origin, nature, and the anticipated loading of potential pollutants. Multiple stormwater management BMPs may be necessary to achieve the established performance standards for water quality, quantity, and groundwater recharge.

**B. Purpose**

It is the purpose of this ordinance to establish minimum stormwater management requirements and controls for major development.

**C. Applicability**

1. This ordinance shall be applicable to any site plan or subdivision that requires preliminary or final site plan review:
  - a. Non-residential major development; and



- b. Aspects of the residential major developments that are not pre-empted by the Residential site Improvements Standards at N.J.A.C. 5:21.
2. This ordinance shall also be applicable to all major developments undertaken by the Mount Arlington Borough.

D. Compatibility with Other Permit and Ordinance Requirements

Development approvals issued pursuant to this ordinance are to be considered an integral part of development approvals under the subdivision and site plan review process and do not relieve the applicant of the responsibility to secure required permits or approvals for activities regulated by any other applicable code, rule, act, or ordinance. In their interpretation and application, the provisions of this ordinance shall be held to be the minimum requirements for the promotion of the public health, safety, and general welfare. This ordinance is not intended to interfere with, abrogate, or annul any other ordinances, rule or regulation, statute, or other provision of law except that, where any provision of this ordinance imposes restrictions different from those imposed by any other ordinance, rule or regulation, or other provision of law, the more restrictive provisions or higher standards shall control.

§17-39.2. Design and Performance Standards for Stormwater Management Measures

1. Stormwater management measures for major development shall be developed to meet the erosion control, groundwater recharge, stormwater runoff quantity, and stormwater runoff quality standards in this section. To the maximum extent feasible, these standards shall be met by incorporating nonstructural stormwater management strategies into the design. If these strategies alone are not sufficient to meet these standards, structural stormwater management measures necessary to meet these standards shall be incorporated into the design.
2. The standards in this ordinance apply only to new major development and are intended to minimize the impact of stormwater runoff on water quality and water quantity in receiving water bodies and maintain groundwater recharge. The standards do not apply to new major development to the extent that alternative design and performance standards are applicable under a regional stormwater management plan or Water Quality Management Plan adopted in accordance with Department rules. Such alternative standards shall provide at least as much protection from stormwater-related loss of groundwater recharge, stormwater quantity and water quality impacts of major development projects as would be provided under the standards in this subchapter.
3. For site improvements regulated under the Residential Site Improvement Standards (RSIS) at N.J.A.C. 5:21, the RSIS shall apply in addition to this section except to the extent the RSIS are superseded by this section or alternative standards applicable under a regional stormwater management



plan or Water Quality Management Plan adopted in accordance with Department rules.

§17-39.3 Stormwater Management Requirements for Major Development

- A. The development shall incorporate a maintenance plan for the stormwater management measures incorporated into the design of a major development.
- B. Stormwater management measures shall avoid adverse impacts of concentrated flow on habitat for threatened and endangered species as documented in the Department' Landscape Project or Natural Heritage Database established under N.J.S.A. 13:1B-15.147 through 15.150, particularly *Helonias bullata* (swamp pink) and/or *Clemmys muhlenbergi* (bog turtle).
- C. The following linear development projects are exempt from the groundwater recharge, stormwater runoff quantity, and stormwater runoff quality requirements at Sections 3.F and 3.G:
  - 1. The construction of an underground utility line provided that the disturbed areas are revegetated upon completion;
  - 2. The construction of an aboveground utility line provided that the existing conditions are maintained to the maximum extent practicable; and
  - 3. The construction of a public pedestrian access, such as a sidewalk or trail with a maximum width of 14 feet, provided that the access is made of permeable material.
- D. A waiver from strict compliance from the groundwater recharge, stormwater runoff quantity, and stormwater runoff quality requirements at Sections 3.F and 3.G may be obtained for the enlargement of an existing public roadway or railroad; or the construction or enlargement of a public pedestrian access, provided that the following conditions are met:
  - 1. The applicant demonstrates that there is a public need for the project that cannot be accomplished by any other means;
  - 2. The applicant demonstrates through an alternatives analysis, that through the use of nonstructural and structural stormwater management strategies and measures, the option selected complies with the requirements of Sections 3.F and 3.G to the maximum extent practicable;
  - 3. The applicant demonstrates that, in order to meet the requirements at Sections 3.F and 3.G, existing structures currently in use, such as homes and buildings would need to be condemned; and

4. The applicant demonstrates that it does not own or have other rights to areas, including the potential to obtain through condemnation lands not falling under D.3 above within the upstream drainage area of the receiving stream, that would provide additional opportunities to mitigate for requirements of Sections 3.F and 3.G that were not achievable on-site.

E. Nonstructural Stormwater Management Strategies

1. To the maximum extent practicable, the standards in 3.F and 3.G shall be met by incorporating nonstructural stormwater management strategies at 3.E into the design. The applicant shall identify the nonstructural measures incorporated into the design of the project. If the applicant contends that it is not feasible for engineering, environmental, or safety reasons to incorporate any nonstructural stormwater management measures identified in 3.E.2 below into the design of a particular project, the applicant shall identify the strategy considered and provide a basis for the contention.
2. Nonstructural stormwater management measures incorporated into site design shall:
  - a. Protect areas that provide water quality benefits or areas particularly susceptible to erosion and sediment loss;
  - b. Minimize impervious surfaces and break up or disconnect the flow of runoff over impervious surfaces;
  - c. Maximize the protection of natural drainage features and vegetation;
  - d. Minimize the decrease in the "time of concentration" from pre-construction to post construction. "Time of concentration" is defined as the time it takes for runoff to travel from the hydraulically most distant point of the watershed to the point of interest within a watershed;
  - e. Minimize land disturbance including clearing and grading;
  - f. Minimize soil compaction;
  - g. Provide low-maintenance landscaping that encourages retention and planting of native vegetation and minimizes the use of lawns, fertilizers and pesticides;
  - h. Provide vegetated open-channel conveyance systems discharging into and through stable vegetated areas;
  - i. Provide other source controls to prevent or minimize the use or exposure of pollutants at the site in order to prevent or minimize the release of those pollutants into stormwater runoff. These source controls include, but are not limited to:
    - (1) Site design features that help to prevent accumulation of trash and debris in drainage systems;
    - (2) Site design features that help to prevent discharge of trash and debris from drainage systems;
    - (3) Site design features that help to prevent and/or contain spills or other harmful accumulations of pollutants at industrial or commercial developments; and



- (4) When establishing vegetation after land disturbance, applying fertilizer in accordance with the requirements established under the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq., and implementing rules.
3. Any land area used as a nonstructural stormwater management measure to meet the performance standards in Sections 3.F and 3.G shall be dedicated to a government agency, subjected to a conservation restriction filed with the appropriate County Clerk's office, or subject to an approved equivalent restriction that ensures that measure or an equivalent stormwater management measure approved by the reviewing agency is maintained in perpetuity.
4. Guidance for nonstructural stormwater management measures is available in the New Jersey Stormwater Best Management Practices Manual. The manual is available on the Department of Environmental Protection's stormwater web page at <http://www.njstormwater.org>.

F. Erosion Control, Groundwater Recharge and Runoff Quantity Standards

1. This section contains minimum design and performance standards to control erosion, encourage and control infiltration and groundwater recharge, and control stormwater runoff quantity impacts of major development.
  - a. The minimum design and performance standards for erosion control are those established under the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq. and implementing rules.
  - b. The minimum design and performance standards for groundwater recharge are as follows:
    - (1) The design engineer shall, using the assumptions and factors for stormwater runoff and groundwater recharge calculations at Section 4, either:
      - (a) Demonstrate through hydrologic and hydraulic analysis that the site and its stormwater management measures maintain 100% of the average annual pre-construction groundwater recharge volume for the site; or
      - (b) Demonstrate through hydrologic and hydraulic analysis that the increase of stormwater runoff volume from pre-construction to post-construction for the 2-year storm is infiltrated.
    - (2) The following types of stormwater shall not be recharged:

- (a) Stormwater from areas of high pollutant loading. High pollutant loading areas are areas in industrial and commercial developments where solvents and/or petroleum products are loaded/unloaded, stored, or applied, areas where pesticides are loaded/unloaded or stored; areas where hazardous materials are expected to be present in greater than 'reportable quantities' as defined by the United States Environmental Protection Agency (EPA) at 40CFR 302.4; areas where recharge would be inconsistent with Department approved remedial action work plan or landfill closure plan and areas with high risks for spills of toxic materials, such as gas stations and vehicle maintenance facilities; and
  - (b) Industrial stormwater exposed to "source material". "Source material" means any material(s) or machinery, located at an industrial facility that is directly or indirectly related to process, manufacturing or other industrial activities, which could be a source of pollutants in any industrial stormwater discharge to groundwater. Source materials include, but are not limited to, raw materials; intermediate products; final products; waste materials; by-products; industrial machinery and fuels, and lubricants, solvents, and detergents that are related to process, manufacturing, or other industrial activities that are exposed to stormwater.
  - (3) The design engineer shall assess the hydraulic impact on the groundwater table and design the site so as to avoid adverse hydraulic impacts. Potential adverse hydraulic impacts include, but are not limited to, exacerbating a naturally or seasonally high water table so as to cause surficial ponding, flooding of basements, or interference with the proper operation of subsurface sewage disposal systems and other subsurface structures in the vicinity or down gradient of the groundwater recharge area.
- c. In order to control stormwater runoff quantity impacts, the design engineer shall, using the assumptions and factors for stormwater runoff calculations at Section 4, complete one of the following:
- (1) Demonstrate through hydrologic and hydraulic analysis that for stormwater leaving the site, post-construction runoff hydrographs for the 2, 10, and 100 year storm events do not exceed, at any point in time, the pre-construction runoff hydrographs for the same storm events;



- (2) Demonstrate through hydrologic and hydraulic analysis that there is no increase, as compared to the pre-construction condition, in the peak runoff rates of stormwater leaving the site for the 2, 10, and 100 year storm events and that the increased volume or change in timing of stormwater runoff will not increase flood damage at or downstream of the site. This analysis shall include the analysis of impacts of existing land uses and projected land uses assuming full development under existing zoning and land use ordinances in the drainage area;
  - (3) Design stormwater management measures so that the post-construction peak runoff rates for the 2, 10 and 100 year storm events are 50, 75 and 80 percent, respectively, of the preconstruction peak runoff rates. The percentages apply only to the post-construction stormwater runoff that is attributable to the portion of the site on which the proposed development or project is to be constructed. The percentages shall not be applied to post-construction stormwater runoff into tidal flood hazard areas if the increased volume of stormwater runoff will not increase flood damages below the point of discharge; or
  - (4) In tidal flood hazard areas, stormwater runoff quantity analysis in accordance with 1, 2 and 3 above shall only be applied if the increased volume of stormwater runoff could increase flood damages below the point of discharge.
2. Any application for a new agricultural development that meets the definition of major development at Section 12 shall be submitted to the appropriate Soil Conservation District for review and approval in accordance with the requirements of this section and any applicable Soil Conservation District guidelines for stormwater runoff quantity and erosion control. For the purposes of this section, "agricultural development" means land uses normally associated with the production of food, fiber and livestock for sale. Such uses do not include the development of land for the processing or sale of food and the manufacturing of agriculturally related products.

#### G. Stormwater Runoff Quality Standards

1. Stormwater management measures shall be designed to reduce the post-construction load of total suspended solids (TSS) in stormwater runoff by 80 percent of the anticipated load from the developed site, expressed as an annual average. Stormwater management measures shall only be required for water quality control if an additional  $\frac{1}{4}$  acre of impervious surface is being proposed on a development site. The requirement to reduce TSS does not apply to any stormwater runoff in a discharge regulated under a numeric effluent limitation for TSS imposed under the New Jersey Pollution Discharge Elimination System (NJPDES) rules, N.J.A.C. 7:14A, or in a discharge

specifically exempt under a NJPDES permit from this requirement. The water quality design storm is 1.25 inches of rainfall in two hours. Water quality calculations shall take into account the distribution of rain from the water quality design storm, as reflected in Table 1. The calculation of the volume of runoff may take into account the implementation of non-structural and structural stormwater management measures.

**Table 1: Water Quality Design Storm Distribution**

<b>Time (Minutes) (inches)</b>	<b>Cumulative Rainfall</b>	<b>Time (Minutes) (inches)</b>	<b>Cumulative Rainfall</b>
0	0.0000	65	0.8917
5	0.0083	70	0.9917
10	0.0166	75	1.0500
15	0.0250	80	1.0840
20	0.0500	85	1.1170
25	0.0750	90	1.1500
30	0.1000	95	1.1750
35	0.1330	100	1.2000
40	0.1660	105	1.2250
45	0.2000	110	1.2334
50	0.2583	115	1.2417
55	0.3583	120	1.2500
60	0.6250		

2. For purposes of TSS reduction calculations, Table 2 below presents the presumed removal rates for certain BMPs designed in accordance with the New Jersey Stormwater Best Management Practices Manual. The BMP Manual may be obtained from the address identified in Section 6, or found on the Department's website at [www.njstormwater.org](http://www.njstormwater.org). The BMP Manual and other sources of technical guidance are listed in Section 6. TSS reduction shall be calculated based on the removal rates for the BMPs in Table 2 below. Alternative removal rates and methods of calculating removal rates may be used if the design engineer provides documentation demonstrating the capability of these alternative rates and methods to the review agency.
3. If more than one BMP in series is necessary to achieve the required 80% TSS reduction for a site, the applicant shall utilize the following formula to calculate TSS reduction:

$$R = A + B - (AXB)/100$$

Where

R = total TSS percent load removal from application of both BMPs, and

A = the TSS percent removal rate applicable to the first BMP

B = the TSS percent removal rate applicable to the second BMP



**Table 2: TSS Removal Rates for BMPs**

<b>Best Management Practice</b>	<b>TSS % Removal Rate</b>
Bioretention Systems	90
Constructed Stormwater Wetland	90
Extended Detention Basin	40-60
Infiltration Structure	80
Manufactured Treatment Device	See Section 5.C
Sand Filter	80
Vegetative Filter Strip	60-80
Wet Pond	50-90

4. If there is more than one onsite drainage area, the 80% TSS removal rate shall apply to each drainage area, unless the runoff from the subareas converge on site in which case the removal rate can be demonstrated through a calculation using a weighted average.
5. Stormwater management measures shall also be designed to reduce, to the maximum extent feasible, the post-construction nutrient load of the anticipated load from the developed site in stormwater runoff generated from the water quality design storm. In achieving reduction of nutrients to the maximum extent feasible, the design of the site shall include nonstructural strategies and structural measures that optimize nutrient removal while still achieving the performance standards in Sections 3.F and 3.G.
6. Additional information and examples are contained in the New Jersey Stormwater Best Management Practices Manual, which may be obtained from the address identified in Section 6.
7. In accordance with the definition of FW1 at N.J.A.C. 7:9B-1.4, stormwater management measures shall be designed to prevent any increase in stormwater runoff to waters classified as FW1.
8. Special water resource protection areas shall be established along all waters designated Category One at N.J.A.C. 7:9B and perennial or intermittent streams that drain into or upstream of the Category One waters as shown on the USGS Quadrangle Maps or in the County Soil Surveys, within the associated HUC14 drainage. These areas shall be established for the protection of water quality, aesthetic value, exceptional ecological significance, exceptional recreational significance, exceptional water supply significance, and exceptional fisheries significance of those established Category One waters. These areas shall be designated and protected as follows:
  - a. The applicant shall preserve and maintain a special water resource protection area in accordance with one of the following:



- (1) A 300-foot special water resource protection area shall be provided on each side of the waterway, measured perpendicular to the waterway from the top of the bank outwards or from the centerline of the waterway where the bank is not defined, consisting of existing vegetation or vegetation allowed to follow natural succession is provided.
  - (2) Encroachment within the designated special water resource protection area under Subsection (1) above shall only be allowed where previous development or disturbance has occurred (for example, active agricultural use, parking area or maintained lawn area). The encroachment shall only be allowed where applicant demonstrates that the functional value and overall condition of the special water resource protection area will be maintained to the maximum extent practicable. In no case shall the remaining special water resource protection area be reduced to less than 150 feet as measured perpendicular to the top of bank of the waterway or centerline of the waterway where the bank is undefined. All encroachments proposed under this subparagraph shall be subject to review and approval by the Department.
- b. All stormwater shall be discharged outside of and flow through the special water resource protection area and shall comply with the Standard For Off-Site Stability in the "Standards for Soil Erosion and Sediment Control in New Jersey", established under the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq.
  - c. If stormwater discharged outside of and flowing through the special water resource protection area cannot comply with the Standard For Off-Site Stability in the "Standards for Soil Erosion and Sediment Control in New Jersey", established under the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq., then the stabilization measures in accordance with the requirements of the above standards may be placed within the special water resource protection area, provided that:
    - (1) Stabilization measures shall not be placed within 150 feet of the Category One waterway;
    - (2) Stormwater associated with discharges allowed by this section shall achieve a 95% TSS postconstruction removal rate;
    - (3) Temperature shall be addressed to ensure no impact on receiving waterway;
    - (4) The encroachment shall only be allowed where the applicant demonstrates that the functional value and overall condition of the

special water resource protection area will be maintained to the maximum extent practicable;

- (5) A conceptual project design meeting shall be held with the appropriate Department staff and Soil Conservation District staff to identify necessary stabilization measures; and
  - (6) All encroachments proposed under this section shall be subject to review and approval by the Department.
- d. A stream corridor protection plan may be developed by a regional stormwater management planning committee as an element of a regional stormwater management plan, or by a municipality through an adopted municipal stormwater management plan. If a stream corridor protection plan for a waterway subject to Section 2.G (8) has been approved by the Department of Environmental Protection, then the provisions of the plan shall be the applicable special water resource protection area requirements for that waterway. A stream corridor protection plan for a waterway subject to G.8 shall maintain or enhance the current functional value and overall condition of the special water resource protection area as defined in G.8.a.(1) above. In no case shall a stream corridor protection plan allow the reduction of the Special Water Resource Protection Area to less than 150 feet as measured perpendicular to the waterway subject to this subsection.
  - e. This subsection does not apply to the construction of one individual single family dwelling that is not part of a larger development on a lot receiving preliminary or final subdivision approval on or before the effective date of the Stormwater Management Rules, provided that the construction begins on or before five years from the effective date of the Stormwater Management Rules.

#### §17-39.4. Calculation of Stormwater Runoff and Groundwater Recharge

- A. Stormwater runoff shall be calculated in accordance with the following:
  - 1. The design engineer shall calculate runoff using one of the following methods:
    - a. The USDA Natural Resources Conservation Service (NRCS) methodology, including the NRCS Runoff Equation and Dimensionless Unit Hydrograph, as described in the NRCS National Engineering Handbook Section 4 – Hydrology and Technical Release 55 – Urban Hydrology for Small Watersheds; or
    - b. The Rational Method for peak flow and the Modified Rational Method for hydrograph computations.



2. For the purpose of calculating runoff coefficients and groundwater recharge, there is a presumption that the pre-construction condition of a site or portion thereof is a wooded land use with good hydrologic condition. The term "runoff coefficient" applies to both the NRCS methodology at Section 4.A.1.a and the Rational and Modified Rational Methods at Section 4.A.1.b. A runoff coefficient or a groundwater recharge land cover for an existing condition may be used on all or a portion of the site if the design engineer verifies that the hydrologic condition has existed on the site or portion of the site for at least five years without interruption prior to the time of application. If more than one land cover have existed on the site during the five years immediately prior to the time of application, the land cover with the lowest runoff potential shall be used for the computations. In addition, there is the presumption that the site is in good hydrologic condition (if the land use type is pasture, lawn, or park), with good cover (if the land use type is woods), or with good hydrologic condition and conservation treatment (if the land use type is cultivation).
3. In computing pre-construction stormwater runoff, the design engineer shall account for all significant land features and structures, such as ponds, wetlands, depressions, hedgerows, or culverts that may reduce pre-construction stormwater runoff rates and volumes.
4. In computing stormwater runoff from all design storms, the design engineer shall consider the relative stormwater runoff rates and/or volumes of pervious and impervious surfaces separately to accurately compute the rates and volume of stormwater runoff from the site. To calculate runoff from unconnected impervious cover, urban impervious area modifications as described in the NRCS Technical Release-55, Urban Hydrology for Small Watersheds and other methods may be employed.
5. If the invert of the outlet structure of a stormwater management measure is below the flood hazard design flood elevation as defined at N.J.A.C. 7:13, the design engineer shall take into account the effects of tailwater in the design of structural stormwater management measures.

B. Groundwater recharge may be calculated in accordance with the following:

1. The New Jersey Geological Survey Geological Survey Report GSR-32 A Method for Evaluating Ground- Water Recharge Areas in New Jersey, incorporated herein by reference as amended and supplemented.

#### §17-39.5. Standards for Structural Stormwater Management Measures

A. Standards for structural stormwater management measures are as follows:

1. Structural stormwater management measures shall be designed to take into account the existing site conditions, including, for example, environmentally critical areas, wetlands; flood-prone areas; slopes; depth to seasonal high



water table; soil type, permeability and texture; drainage area and drainage patterns; and the presence of solution-prone carbonate rocks (limestone).

2. Structural stormwater management measures shall be designed to minimize maintenance, facilitate maintenance and repairs, and ensure proper functioning. Trash racks shall be installed at the intake to the outlet structure as appropriate, and shall have parallel bars with one-inch (1") spacing between the bars to the elevation of the water quality design storm. For elevations higher than the water quality design storm, the parallel bars at the outlet structure shall be spaced no greater than one-third (1/3) the width of the diameter of the orifice or one-third (1/3) the width of the weir, with a minimum spacing between bars of one-inch and a maximum spacing between bars of six inches. In addition, the design of trash racks must comply with the requirements of Section 7.D.
  3. Structural stormwater management measures shall be designed, constructed, and installed to be strong, durable, and corrosion resistant. Measures that are consistent with the relevant portions of the Residential Site Improvement Standards at N.J.A.C. 5:21-7.3, 7.4, and 7.5 shall be deemed to meet this requirement.
  4. At the intake to the outlet from the stormwater management basin, the orifice size shall be a minimum of two and one-half inches in diameter.
  5. Stormwater management basins shall be designed to meet the minimum safety standards for stormwater management basins at Section 7.
- B. Stormwater management measure guidelines are available in the New Jersey Stormwater Best Management Practices Manual. Other stormwater management measures may be utilized provided the design engineer demonstrates that the proposed measure and its design will accomplish the required water quantity, groundwater recharge and water quality design and performance standards established by this subchapter.
- C. Manufactured treatment devices may be used to meet the requirements of this subchapter, provided the pollutant removal rates are verified by the New Jersey Corporation for Advanced Technology and certified by the Department.

#### §17-39.6. Sources for Technical Guidelines

- A. Technical guidance for stormwater management measures can be found in the documents listed at 1 and 2 below, which are available from Maps and Publications, Department of Environmental Protection, 428 East State Street, P.O. Box 420, Trenton, New Jersey, 08625; telephone (609) 777-1038.
1. Guidelines for stormwater management measures are contained in the New Jersey Stormwater Best Management Practices Manual, as amended.

Information is provided on stormwater management measures such as: bioretention systems, constructed stormwater wetlands, dry wells, extended detention basins, infiltration structures, manufactured treatment devices, pervious paving, sand filters, vegetative filter strips, and wet ponds.

2. The New Jersey Department of Environmental Protection Stormwater Management Facilities Maintenance Manual, as amended.
- B. Additional technical guidance for stormwater management measures can be obtained from the following:
1. The “Standards for Soil Erosion and Sediment Control in New Jersey” promulgated by the State Soil Conservation Committee and incorporated into N.J.A.C. 2:90. Copies of these standards may be obtained by contacting the Soil Conservation District.
  2. The Rutgers Cooperative Extension Service; and
  3. The Soil Conservation Districts

#### §17-39.7. Safety Standards for Stormwater Management Basins

- A. This section sets forth requirements to protect public safety through the proper design and operation of stormwater management basins. This subchapter applies to any new stormwater management basin.
- B. The provisions of this section are not intended to preempt more stringent municipal or county safety requirements for new or existing stormwater management basins.
- C. Requirements for Trash Racks, Overflow Grates and Escape Provisions
1. A trash rack is a device designed to catch trash and debris and prevent the clogging of outlet structures. Trash racks shall be installed at the intake to the outlet from the stormwater management basin to ensure proper functioning of the basin outlets in accordance with the following:
    - a. The trash rack shall have parallel bars, with no greater than six inch spacing between the bars.
    - b. The trash rack shall be designed so as not to adversely affect the hydraulic performance of the outlet pipe or structure.
    - c. The average velocity of flow through a clean trash rack is not to exceed 2.5 feet per second under the full range of stage and discharge. Velocity is to be computed on the basis of the net area of opening through the rack.
    - d. The trash rack shall be constructed and installed to be rigid, durable, and corrosion resistant, and shall be designed to withstand a perpendicular live loading of 300 lbs/ft sq.



2. An overflow grate is designed to prevent obstruction of the overflow structure. If an outlet structure has an overflow grate, such grate shall meet the following requirements:
  - a. The overflow grate shall be secured to the outlet structure but removable for emergencies and maintenance.
  - b. The overflow grate spacing shall be no less than two inches across the smallest dimension.
  - c. The overflow grate shall be constructed and installed to be rigid, durable, and corrosion resistant, and shall be designed to withstand a perpendicular live loading of 300 lbs/ft sq.
3. For purposes of this subsection, escape provisions means the permanent installation of ladders, steps, rungs, or other features that provide easily accessible means of egress from stormwater management basins. Stormwater management basins shall include escape provisions as follows:
  - a. If a stormwater management basin has an outlet structure, escape provisions shall be incorporated in or on the structure. With the prior approval of the reviewing agency identified in Section 7.D a freestanding outlet structure may be exempted from this requirement.
  - b. Safety ledges shall be constructed on the slopes of all new stormwater management basins having a permanent pool of water deeper than two and one-half feet. Such safety ledges shall be comprised of two steps. Each step shall be four to six feet in width. One step shall be located approximately two and one-half feet below the permanent water surface, and the second step shall be located one to one and one-half feet above the permanent water surface. See Section 7.E for an illustration of safety ledges in a stormwater management basin.
  - c. In new stormwater management basins, the maximum interior slope for an earthen dam, embankment, or berm shall not be steeper than 3 horizontal to 1 vertical.

D. Variance or Exemption from Safety Standards

1. A variance or exemption from the safety standards for stormwater management basins may be granted only upon a written finding by the appropriate reviewing agency (municipality, county or Department) that the variance or exemption will not constitute a threat to public safety.

§17-39.8. Requirements for a Site Development Stormwater Plan

A. Submission of Site Development Stormwater Plan



1. Whenever an applicant seeks municipal approval of a development subject to this ordinance, the applicant shall submit all of the required components of the Checklist for the Site Development Stormwater Plan at 8.C below as part of the submission of the applicant's application for subdivision or site plan approval.
2. The applicant shall demonstrate that the project meets the standards set forth in this ordinance.
3. The applicant shall submit 15 copies of the materials listed in the checklist for site development stormwater plans in accordance with Section 8.C of this ordinance.

#### B. Site Development Stormwater Plan Approval

The applicant's Site Development project shall be reviewed as a part of the subdivision or site plan review process by the municipal board or official from which municipal approval is sought. That Municipal board or official shall consult the engineer retained by the Land Use Board to determine if all the checklist requirements have been satisfied and to determine if the project meets the standards set forth in this ordinance.

#### C. Checklist Requirements

The following information shall be required:

##### 1. Topographic Base Map

The reviewing engineer may require upstream tributary drainage system information as necessary. It is recommended that the topographic base map of the site be submitted which extends a minimum of 200 feet beyond the limits of the proposed development, at a scale of 1"=200' or greater, showing 2- foot contour intervals. The map as appropriate may indicate the following: existing surface water drainage, shorelines, steep slopes, soils, erodible soils, perennial or intermittent streams that drain into or upstream of the Category 1 waters, wetlands and flood plains along with their appropriate buffer strips, marshlands and other wetlands, pervious or vegetative surfaces, existing man-made structures, roads, bearing and distances of property lines, and significant natural and manmade features not otherwise shown.

##### 2. Environmental Site Analysis

A written and graphic description of the natural and man-made features of the site and its environs. This description should include a discussion of soil conditions, slopes, wetlands, waterways and vegetation on the site. Particular attention should be given to unique, unusual, or environmentally sensitive features and to those that provide particular opportunities or constraints for development.

### 3. Project Description and Site Plan(s)

A map (or maps) at the scale of the topographical base map indicating the location of existing and proposed buildings, roads, parking areas, utilities, structural facilities for stormwater management and sediment control, and other permanent structures. The map(s) shall also clearly show areas where alterations occur in the natural terrain and cover, including lawns and other landscaping, and seasonal high ground water elevations. A written description of the site plan and justification of proposed changes in natural conditions may also be provided.

### 4. Land Use Planning and Source Control Plan

This plan shall provide a demonstration of how the goals and standards of Sections 2 through 5 are being met. The focus of this plan shall be to describe how the site is being developed to meet the objective of controlling groundwater recharge, stormwater quality and stormwater quantity problems at the source by land management and source controls whenever possible.

### 5. Stormwater Management Facilities Map

The following information, illustrated on a map of the same scale as the topographic base map, shall be included:

- a. Total area to be paved or built upon, proposed surface contours, land area to be occupied by the stormwater management facilities and the type of vegetation thereon, and details of the proposed plan to control and dispose of stormwater.
- b. Details of all stormwater management facility designs, during and after construction, including discharge provisions, discharge capacity for each outlet at different levels of detention and emergency spillway provisions with maximum discharge capacity of each spillway.

### 6. Calculations

- a. Comprehensive hydrologic and hydraulic design calculations for the pre-development and postdevelopment conditions for the design storms specified in Section 3 of this ordinance.
- b. When the proposed stormwater management control measures (e.g. infiltration basins) depend on the hydrologic properties of soils, then a soils report shall be submitted. The soils report shall be based on onsite boring logs or soil pit profiles. The number and location of required soil borings or soil pits shall be determined based on what is needed to determine the suitability and distribution of soil types present at the location of the control measure.



## 7. Maintenance and Repair Plan

The design and planning of the stormwater management facility shall meet the maintenance requirements of Section 9.

## 8. Waiver from Submission Requirements

The municipal official or board reviewing an application under this ordinance may, in consultation with the municipal engineer, waive submission of any of the requirements in Sections 8.C.1 through 8.C.6 of this ordinance when it can be demonstrated that the information requested is impossible to obtain or it would create a hardship on the applicant to obtain and its absence will not materially affect the review process.

### §17-39.9. Maintenance and Repair

#### A. Applicability

1. Projects subject to review as in Section 1.C of this ordinance shall comply with the requirements of Section 9.B and 9.C.

#### B. General Maintenance

1. The design engineer shall prepare a maintenance plan for the stormwater management measures incorporated into the design of a major development.
2. The maintenance plan shall contain specific preventative maintenance tasks and schedules; cost estimates, including estimated cost of sediment, debris, or trash removal; and the name, address, and telephone number of the person or persons responsible for preventative and corrective maintenance (including replacement). Maintenance guidelines for stormwater management measures are available in the New Jersey Stormwater Best Management Practices Manual. If the maintenance plan identifies a person other than the developer (for example, a public agency or homeowners' association) as having the responsibility for maintenance, the plan shall include documentation of such person's agreement to assume this responsibility, or of the developer's obligation to dedicate a stormwater management facility to such person under an applicable ordinance or regulation.
3. Responsibility for maintenance shall not be assigned or transferred to the owner or tenant of an individual property in a residential development or project, unless such owner or tenant owns or leases the entire residential development or project.
4. If the person responsible for maintenance identified under Section 9.B.2 above is not a public agency, the maintenance plan and any future revisions based on Section 9.B.7 below shall be recorded upon the deed of record for



each property on which the maintenance described in the maintenance plan must be undertaken.

5. Preventative and corrective maintenance shall be performed to maintain the function of the stormwater management measure, including repairs or replacement to the structure; removal of sediment, debris, or trash; restoration of eroded areas; snow and ice removal; fence repair or replacement; restoration of vegetation; and repair or replacement of nonvegetated linings.
  6. The person responsible for maintenance identified under Section 9.B.2 above shall maintain a detailed log of all preventative and corrective maintenance for the structural stormwater management measures incorporated into the design of the development, including a record of all inspections and copies of all maintenance-related work orders.
  7. The person responsible for maintenance identified under Section 9.B.2 above shall evaluate the effectiveness of the maintenance plan at least once per year and adjust the plan and the deed as needed.
  8. The person responsible for maintenance identified under Section 9.B.2 above shall retain and make available, upon request by any public entity with administrative, health, environmental, or safety authority over the site, the maintenance plan and the documentation required by Sections 9.B.6 and 9.B.7 above.
  9. The requirements of Sections 9.B.3 and 9.B.4 do not apply to stormwater management facilities that are dedicated to and accepted by the municipality or another governmental agency.
  10. In the event that the stormwater management facility becomes a danger to public safety or public health, or if it is in need of maintenance, the municipality shall so notify the responsible person in writing. Upon receipt of that notice, the responsible person shall have fourteen (14) days to effect maintenance and repair of the facility in a manner that is approved by the municipal engineer or his designee. If the responsible person fails or refuses to perform such maintenance and repair, the municipality or County may immediately proceed to do so and shall bill the cost thereof to the responsible person.
- C. Nothing in this section shall preclude the municipality in which the major development is located from requiring the posting of a performance or maintenance guarantee in accordance with N.J.S.A. 40:55D-53.

#### §17-39.10. Definitions

Unless specifically defined below, words or phrases used in this section shall be interpreted so as to give them the meaning they have in common usage and to give this ordinance its most reasonable application.

“Compaction” means the increase in soil bulk density.

“Core” means a pedestrian-oriented area of commercial and civic uses serving the surrounding municipality, generally including housing and access to public transportation.

“County review agency” means an agency designated by the County Board of Chosen Freeholders to review municipal stormwater management plans and implementing ordinance(s). The county review agency may either be:

A county planning agency; or

A county water resource association created under N.J.S.A 58:16A-55.5, if the ordinance or resolution delegates authority to approve, conditionally approve, or disapprove municipal stormwater management plans and implementing ordinances.

“Department” means the New Jersey Department of Environmental Protection.

“Designated Center” means a State Development and Redevelopment Plan Center as designated by the State Planning Commission such as urban, regional, town, village, or hamlet.

“Design engineer” means a person professionally qualified and duly licensed in New Jersey to perform engineering services that may include, but not necessarily be limited to, development of project requirements, creation and development of project design and preparation of drawings and specifications.

“Development” means the division of a parcel of land into two or more parcels, the construction, reconstruction, conversion, structural alteration, relocation or enlargement of any building or structure, any mining excavation or landfill, and any use or change in the use of any building or other structure, or land or extension of use of land, for which permission is required under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq. In the case of development of agricultural lands, development means: any activity that requires a State permit; any activity reviewed by the County Agricultural Board (CAB) and the State Agricultural Development Committee (SADC), and municipal review of any activity not exempted by the Right to Farm Act, N.J.S.A 4:1C-1 et seq.

“Drainage area” means a geographic area within which stormwater, sediments, or dissolved materials drain to a particular receiving waterbody or to a particular point along a receiving waterbody.



“Environmentally constrained area” means the following areas where the physical alteration of the land is in some way restricted, either through regulation, easement, deed restriction or ownership such as: wetlands, floodplains, threatened and endangered species sites or designated habitats, and parks and preserves. Habitats of endangered or threatened species are identified using the Department’s Landscape Project as approved by the Department’s Endangered and Nongame Species Program.

“Environmentally critical areas” means an area or feature which is of significant environmental value, including but not limited to: stream corridors; natural heritage priority sites; habitat of endangered or threatened species; large areas of contiguous open space or upland forest; steep slopes; and well head protection and groundwater recharge areas. Habitats of endangered or threatened species are identified using the Department’s Landscape Project as approved by the Department’s Endangered and Nongame Species Program.

“Erosion” means the detachment and movement of soil or rock fragments by water, wind, ice or gravity.

“Impervious surface” means a surface that has been covered with a layer of material so that it is highly resistant to infiltration by water.

“Infiltration” is the process by which water that seeps into the soil from precipitation.

“Major development” means any “development” that provides for ultimately disturbing one or more acres of land or increasing impervious surface by one-quarter acre or more. Disturbance for the purpose of this rule is the placement of impervious surface or exposure and/or movement of soil or bedrock or clearing, cutting, or removing of vegetation. Projects undertaken by any government agency which otherwise meet the definition of “major development” but which do not require approval under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq. are also considered “major development.”

“Municipality” means Mount Arlington Borough.

“Node” means an area designated by the State Planning Commission concentrating facilities and activities, which are not organized in a compact form.

“Nutrient” means a chemical element or compound, such as nitrogen or phosphorus, which is essential to and promotes the development of organisms.

“Person” means any individual, corporation, company, partnership, firm, association, or political subdivision of this State and any state, interstate or federal agency.

“Pollutant” means any dredged spoil, solid waste, incinerator residue, filter backwash, sewage, garbage, refuse, oil, grease, sewage sludge, munitions, chemical wastes, biological materials, medical wastes, radioactive substance (except those regulated under the Atomic Energy Act of 1954, as amended (42 U.S.C. 2011 et seq.), thermal



waste, wrecked or discarded equipment, rock, sand, cellar dirt, industrial, municipal, agricultural, and construction waste or runoff, or other residue discharged directly or indirectly to the land, ground waters or surface waters of the State, or to a domestic treatment works.

“Pollutant” includes both hazardous and nonhazardous pollutants.

“Recharge” means the amount of water from precipitation that infiltrates into the ground and is not evapotranspired.

“Sediment” means solid material, mineral or organic, that is in suspension, is being transported, or has been moved from its site of origin by air, water or gravity as a product of erosion.

“Site” means the lot or lots upon which a major development is to occur or has occurred.

“Soil” means all unconsolidated mineral and organic material of any origin.

“State Plan Policy Map” is defined as the geographic application of the State Development and Redevelopment Plan’s goals and statewide policies, and the official map of these goals and policies.

“Stormwater” means water resulting from precipitation (including rain and snow) that runs off the land’s surface, is transmitted to the subsurface, or is captured by separate storm sewers or other sewage or drainage facilities.

“Stormwater runoff” means water flow on the surface of the ground or in storm sewers, resulting from precipitation.

“Stormwater management basin” means an excavation or embankment and related areas designed to retain stormwater runoff. A stormwater management basin may either be normally dry (that is, a detention basin or infiltration basin), retain water in a permanent pool (a retention basin), or be planted mainly with wetland vegetation (most constructed stormwater wetlands).

“Stormwater management measure” means any structural or nonstructural strategy, practice, technology, process, program, or other method intended to control or reduce stormwater runoff and associated pollutants, or to induce or control the infiltration or groundwater recharge of stormwater or to eliminate illicit or illegal non-stormwater discharges into stormwater conveyances.

“Wetlands” or “wetland” means an area that is inundated or saturated by surface water or ground water at a frequency and duration sufficient to support, and that under normal circumstances does support, a prevalence of vegetation typically adapted for life in saturated soil conditions, commonly known as hydrophytic vegetation.

**SECTION 3.** If any article, section, subsection, paragraph, phrase, or sentence is for any reason held to be unconstitutional or invalid, said article, section, subsection, paragraph, phrase or sentence shall be deemed separable.

**SECTION 4.** This Ordinance shall take effect upon final publication as provided by law.

I **HEREBY CERTIFY** this to be a true and correct Ordinance of the Mayor and Borough Council of the Borough of Mount Arlington, adopted on January 31, 2005 and will be further considered after a Public Hearing held on \* March 29, 2005 at the Municipal Building at 7:00 p.m.


INTRODUCED: 1/31/05

PUBLISHED:

ATTEST:

BOROUGH OF MOUNT ARLINGTON  
COUNTY OF MORRIS  
STATE OF NEW JERSEY

  
Linda DeSantis, Borough Clerk


  
Arthur R. Ondish, Mayor  
Borough of Mount Arlington

\* to be determined after  
Land Use Approval -

\* See Land Use letter of 3/24/05 attached  
to Ordinance



**Figure C-2: Borough of Mount Arlington  
and its Waterways**  
Morris County, New Jersey



2,000 1,000 0 2,000 4,000  
Feet  
1 Inch equals 2,000 Feet



**Suburban Consulting  
Engineers, Inc.**


- Civil Engineers - Municipal Engineers -  
- Planners - Environmentalists - Land Surveyors -

100 Valley Road, Suite 202, Mt. Arlington, N.J. 07856 973.398.1776

DRAWN BY: J.J.W.	CHECKED BY: D.J.P.	DATE: 12/14/04	SCALE: 1" = 2000'	PROJECT NO. SCE-2485.1
---------------------	-----------------------	-------------------	----------------------	---------------------------




**Figure C-2A: Borough of Mount Arlington and its Waterways by Surface Water Quality Classification Morris County, New Jersey**





**Figure C-3: Borough of Mount Arlington on  
USGS Quadrangles  
Morris County, New Jersey**



Source:  
- NJ DEP  
- US Geological Survey  
SE Stanhope & SW Dover  
Quadrangles.

### Legend



Municipal Boundary

This Map Is Intended For Planning Purposes Only.  
This Map Was Developed Using New Jersey  
Department Of Environmental Protection  
Geographic Information System Digital Data, But This  
Secondary Product Has Not Been Verified By Suburban  
Consulting Engineers, Inc.



**Suburban Consulting  
Engineers, Inc.**

- Civil Engineers - Municipal Engineers -  
- Planners - Environmentalists - Land Surveyors -

100 Valley Road, Suite 202, Mt. Arlington, N.J. 07856 973.398.1776

DRAWN BY:  
J.J.W.

CHECKED BY:  
D.J.P.

DATE:  
12/14/04


SCALE:  
1" = 2000'

PROJECT NO.  
SCE-2485.1

2,000 1,000 0 2,000 4,000  
Feet  
1 Inch equals 2,000 Feet



**Figure C-4: Groundwater Recharge Areas In  
The Borough of Mount Arlington  
Morris County, New Jersey**



2,000 1,000 0 2,000 4,000  
Feet  
1 Inch equals 2,000 Feet



**Suburban Consulting  
Engineers, Inc.**


- Civil Engineers - Municipal Engineers -  
- Planners - Environmentalists - Land Surveyors -

100 Valley Road, Suite 202, Mt. Arlington, N.J. 07856 973.398.1776

DRAWN BY: J.J.W.	CHECKED BY: D.J.P.	DATE: 12/14/04	SCALE: 1" = 2000'	PROJECT NO. SCE-2485.1
---------------------	-----------------------	-------------------	----------------------	---------------------------



**Figure C-5: Wellhead Protection Areas in the Borough of Mount Arlington Morris County, New Jersey**



2,000 1,000 0 2,000 4,000  
Feet  
1 Inch equals 2,000 Feet



**Suburban Consulting Engineers, Inc.**

- Civil Engineers - Municipal Engineers -  
- Planners - Environmentalists - Land Surveyors -

100 Valley Road, Suite 202, Mt. Arlington, N.J. 07856 973.398.1776

DRAWN BY:  
J.J.W.

CHECKED BY:  
D.J.P.


DATE:  
12/14/04

SCALE:  
1" = 2000'

PROJECT NO.  
SCE-2485.1




**Figure C-6: Borough of Mount Arlington  
Existing Land Use  
Morris County, New Jersey**





**Figure C-7: NJ GS Watersheds by 14-Digit Hydrologic Unit Codes (HUC14s) Within the Borough of Mount Arlington Morris County, New Jersey**



2,000 1,000 0 2,000 4,000 Feet  
1 Inch equals 2,000 Feet



**Suburban Consulting Engineers, Inc.**

- Civil Engineers - Municipal Engineers -  
- Planners - Environmentalists - Land Surveyors -

100 Valley Road, Suite 202, Mt. Arlington, N.J. 07856 973.398.1776

DRAWN BY:  
J.J.W.

CHECKED BY:  
D.J.P.


DATE:  
12/14/04

SCALE:  
1" = 2000'

PROJECT NO  
SCE-2485.1




**Figure C-8: Zoning Districts Within  
The Borough of Mount Arlington  
Morris County, New Jersey**







**Figure C-9: Constrained Land Within  
The Borough of Mount Arlington  
Morris County, New Jersey**



Source:  
 - NJ DEP.  
 - County of Morris, Department  
 of Planning and Development.  
 - GI, September 2002, Parcels  
 and Municipal Boundary.  
 - Geographic Information Systems  
 Section, Hydrography\_Area and  
 Hydrography\_Linear.  
 - NJDEP 1995/97 Land use/Land  
 cover Update, Upper Delaware  
 Watershed Management Area  
 WMA-1, Whippany and  
 Rockaway Watershed  
 Management Area WMA-6,  
 North and South Branch  
 Raritan Watershed  
 Management Area WMA-8.  
 - Highlands Water Protection  
 and Planning Act, NJ  
 Highlands Preservation and  
 Planning Area, Highlands.



**NJ DEP Land Use / Cover 1995 / 97**

-  WATER
-  WETLANDS

**Highlands**

-  Highlands Planning Area
-  Highlands Preservation Area

This Map Is Intended For Planning Purposes Only.  
 This Map Was Developed Using New Jersey  
 Department Of Environmental Protection  
 Geographic Information System Digital Data, But This  
 Secondary Product Has Not Been Verified By Suburban  
 Consulting Engineers, Inc.

2,000 1,000 0 2,000 4,000  
 Feet  
 1 Inch equals 2,000 Feet



**Suburban Consulting  
Engineers, Inc.**

- Civil Engineers - Municipal Engineers -  
 - Planners - Environmentalists - Land Surveyors -

100 Valley Road, Suite 202, Mt. Arlington, N.J. 07856 973.398.1776

DRAWN BY: J.J.W.	CHECKED BY: D.J.P.	DATE: 12/14/04	SCALE: 1" = 2000'	PROJECT NO. SCE-2485.1
---------------------	-----------------------	-------------------	----------------------	---------------------------